# **REFLEX**

## REVERSIBLE SOLID OXIDE ELECTROLYZER AND FUEL CELL FOR OPTIMIZED LOCAL ENERGY MIX





#### **PROJECT AND OBJECTIVES**

REFLEX aims to develop an innovative renewable energy storage solution, based on reversible solid oxide cell (rSOC) technology, that can operate in either electrolysis mode, to store excess electricity to produce  $H_{\rm 2}$ , or fuel cell mode, when energy needs exceed local production levels, to produce electricity and heat from  $H_{\rm 2}$  or any other fuel that is locally available. It has developed improved rSOC components (cells, stacks, power electronics, heat exchangers) and has defined the system, its set points and advanced operation strategies. An in-field demonstration will be performed in 2023.

#### **NON-OUANTITATIVE OBJECTIVES**

- The project aims to complete a techno-economic assessment.
- It also aims to create an inventory of regulations, codes and standards applicable to rSOC systems in France and Italy.

#### **PROGRESS AND MAIN ACHIEVEMENTS**

- · Enlarged cells were produced.
- The project has improved the stack for rSOC operation.
- · The rSOC module design was completed.
- The rSOC module assembly has started.
- The site integration is almost complete.

#### **FUTURE STEPS AND PLANS**

- The modules and system assembly are being finalised.
- The installation of the system for an in-field test was planned for 2023.

### http://www.reflex-energy.eu/

#### **QUANTITATIVE TARGETS AND STATUS**

Target source	Parameter	Unit	Target	Achieved to date by the project	Target achieved?	SoA result achieved to date (by others)	Year of SoA target
Project's own objectives	Current density in SOEC mode	A/cm <sup>2</sup>	1.2	N/A		– 1.15 at 750 °C, – 1 at 800 °C	2015-2016
	Durability in SOEC step during rSOC operation at 0.58 A/cm <sup>2</sup> and SC = 68 %	%/1 000 h	2	1.2	Ş	2.3 for current densities of 0.6-0.7 A/cm <sup>2</sup> and SC = 50 %	2015
	Cell active area	cm <sup>2</sup>	200	200	<b>✓</b>	128	2021
	Power electronic efficiency	%	95	96	<b>✓</b>	88	2019
	Power modulation SC = 80 %	%	50-100 (SOFC), 70-100 (SOEC)	58-100 in SOEC, 13-100 in natural- gas SOFC and 23-100 in H <sub>2</sub> SOFC		57-100 in SOEC	2019



